

Claims

1. (previously presented) A method for managing alternate site switching in an optical communication system having a protected end-system in communication with a primary end-system over an optical communication network, the method comprising:

designating at least one backup end-system to back up the primary end-system;

constructing a failover tree through the optical communication system to the at least one backup end-system prior to a detection of a degradation or failure affecting the primary end-system;

forwarding communications from the protected end-system to the primary end-system;

detecting a degradation or failure affecting the primary end-system;

and

upon detection of the degradation or failure affecting the primary end-system, switching traffic from forwarded by the protected end-system to the primary end-system to one of said at least one backup end-system using the failover tree,

wherein constructing a failover tree to the at least one backup end-system comprises:

determining a root node for the failover tree; and constructing the failover tree rooted at the root node, and

wherein constructing the failover tree rooted at the root node comprises:

sending a setup request message specifying a failover tree structure to various nodes in the optical communication network;

reserving appropriate lightpath resources by nodes associated with a lightpath to the primary end-system; and

recording the failover tree structure by nodes associated with the failover tree.

2. (original) The method of claim 1, wherein designating at least one backup end-system to back up the primary end-system comprises:

receiving a setup request from the protected end-system specifying the at least one backup end-system.

3. (original) The method of claim 1, wherein designating at least one backup end-system to back up the primary end-system comprises:

automatically discovering the at least one backup end-system using a predetermined auto-discovery mechanism.

4. (cancelled)

5. (previously presented) The method of claim 1, wherein determining a root node for the failover tree comprises:

identifying a candidate node that is within a predetermined distance from the at least one backup end-system;

constructing a shortest-path spanning tree from the candidate node to the at least one backup end-system; and

selecting the candidate node as the root node if-and only if the shortest-path spanning tree does not include any link from the protected end-system to the candidate node.

6. (original) The method of claim 5, wherein identifying a candidate node that is within a predetermined distance from the backup end-system comprises:

using a marking scheme to identify the candidate node.

7. (original) The method of claim 5, wherein identifying a candidate node that is within a predetermined distance from the backup end-system comprises:

solving a geometrical problem to identify the candidate node.

8. (original) The method of claim 5, wherein constructing a shortest-path spanning tree from the candidate node to the at least one backup end-system comprises:

constructing the shortest-path spanning tree from the candidate node to the at least one backup end-system based upon topology information obtained from a routing protocol.

9. (cancelled)

10. (original) The method of claim 1, wherein detecting a degradation or failure affecting the primary end-system comprises at least one of:

- monitoring a bearer channel between the primary end-system and a corresponding edge node in the optical communication network; and

- querying the primary end-system by an optical-service agent in said corresponding edge node.

11. (original) The method of claim 1, wherein switching traffic from the primary end-system to one of said at least one backup end-systems comprises:

- determining a failover node along the failover tree in the optical communication network;
- establishing a backup lightpath from the failover node to a backup end-system; and
- switching traffic to the backup lightpath by the failover node.

12. (original) The method of claim 11, wherein determining a failover node along the failover tree in the optical communication network comprises:

- propagating a release message upstream from a primary edge node associated with the primary end-system toward a predetermined root node of the failover tree;

- receiving the release message by an intermediate node between the predetermined root node and the primary end-system; and

- determining by said intermediate node that the intermediate node supports a backup end-system.

13. (original) The method of claim 11, wherein establishing a backup lightpath from the failover node to a backup end-system comprises:

- sending a lightpath setup request message by the failover node downstream toward the backup end-system; and

- reserving appropriate lightpath resources by a number of nodes between the failover node and the backup end-system.

14. (original) The method of claim 11, wherein switching traffic to the backup lightpath by the failover node comprises:

 sending a connect message by a backup edge node associated with the backup end-system to the failover node; and

 switching traffic to the backup lightpath by the failover node upon receiving said connect message.

15. (original) The method of claim 11, further comprising:

 relinquishing lightpath resources by a number of nodes from the failover node to the primary end-system.

16. (original) The method of claim 1, further comprising:

 determining that the primary end-system is available; and switching traffic back to the primary end-system.

17. (original) The method of claim 1, further comprising:

 determining that the primary end-system is available; and designating the primary end-system to back up the backup end-system.

18. (currently amended) A Apparatus comprising:

_____ a device for managing alternate site switching in an optical communication system having a protected end-system in communication with a primary end-system over an optical communication network, including the device comprising: backup end-system designation logic operably coupled to designate at least one backup end-system to back up the primary end-system; and failover tree construction logic operably coupled to construct a failover tree to the at least one backup end-system prior to detection of actual failure or degradation of the primary end-system, wherein the failover tree construction logic is operably coupled to determine a root node for the failover tree and construct the failover tree rooted at the root node, and wherein the failover tree construction logic is operably coupled to construct the failover tree rooted at the root

node by sending a setup request message specifying a failover tree structure to various nodes in the optical communication network.

19. (currently amended) The apparatus ~~device~~ of claim 18, wherein the backup end-system designation logic is operably coupled to receive the ~~a~~ setup request from the protected end-system specifying the at least one backup end-system.

20. (currently amended) The apparatus ~~device~~ of claim 18, wherein the backup end-system designation logic is operably coupled to automatically discover the at least one backup end-system using a predetermined auto-discovery mechanism.

21. (cancelled)

22. (currently amended) The apparatus ~~device~~ of claim 18, wherein the failover tree construction logic is operably coupled to determine a root node for the failover tree by identifying a candidate node that is within a predetermined distance from the at least one backup end-system, constructing a shortest-path spanning tree from the candidate node to the at least one backup end-system, and selecting the candidate node as the root node if and only if the shortest-path spanning tree does not include any link from the protected end-system to the candidate node.

23. (currently amended) The apparatus ~~device~~ of claim 22, wherein the failover tree construction logic uses a marking scheme to identify the candidate node.

24. (currently amended) The apparatus ~~device~~ of claim 11, wherein the failover tree construction logic solves a geometrical problem to identify the candidate node.

25. (currently amended) The apparatus ~~device~~ of claim 22, wherein the failover tree construction logic constructs the shortest-path spanning tree from the candidate node to the at least one backup end-system based upon topology information obtained from a routing protocol.

26. (cancelled)

27. (currently amended) ~~A~~ Apparatus comprising:

_____ a device for managing alternate site switching in an optical communication system having a protected end-system in communication with a primary end-system over an optical communication network, including the device comprising: a failover tree database for recording the structure of a failover tree having at least a root node, the failover tree computed prior to a detection of a degradation or failure affecting the primary-end system; detection logic operably coupled to detect a the degradation or failure affecting the primary end-system; and signaling logic operably coupled to send a release message upstream toward the root node over the failover tree when the detection logic detects the degradation or failure affecting the primary end-system to release light-path resources to the primary end-system.

28. (currently amended) The apparatus device of claim 17, wherein the detection logic is operably coupled to detect a degradation or failure affecting the primary end-system by at least one of:

monitoring a bearer channel to the primary end-system; and
querying the primary end-system.

29. (currently amended) The apparatus device of claim 27, further comprising:

lightpath logic operably coupled to relinquish lightpath resources associated with a primary lightpath to the primary end-system.

30. (currently amended) ~~A~~ Apparatus comprising:

_____ a device for managing alternate site switching in an optical communication system having a protected end-system in communication with a primary end-system over an optical communication network, including the device comprising: a failover tree database for recording the structure of a failover tree having a backup end-system, the failover tree being identified prior to failure of the primary end-system; first receiving logic operably coupled to receive a release message; and switching logic operably coupled to switch traffic from a primary end-system to a

backup end-system using the prior constructed failover tree when the first receiving logic receives the release message.

31. (currently amended) The apparatus device of claim 30, wherein the switching logic is operably coupled to send a lightpath setup request message downstream toward the backup end-system to establish a backup lightpath, reserve lightpath resources for the backup lightpath, and switch traffic to the backup lightpath.

32. (currently amended) ~~An~~ Apparatus comprising:

_____ an optical communication system for managing alternate site switching, the optical communication system comprising a plurality of end-systems including a protected end-system, a primary end-system, and at least one backup end-system coupled over an optical communication network, wherein each end-system interfaces with the optical communication network through a corresponding optical edge node, and wherein a failover tree is constructed to the at least one backup end-system prior to a detection of a failure of the primary end-system, and traffic is switched from the primary end-system to a backup end-system upon detecting a degradation or failure affecting the primary end-system; ; wherein the optical edge node associated with the primary end-system is operably coupled to: detect a degradation or failure affecting the primary end-system; ; ~~and wherein the optical edge node associated with the primary end-system is operably coupled to~~ send a release message upstream toward a root node of the failover tree upon detecting a degradation or failure affecting the primary end-system.

33. (currently amended) The apparatus optical communication system of claim 32, wherein the protected end-system is operably coupled to send a setup request message to its corresponding optical edge node indicating the at least one backup end-system.

34. (currently amended) The apparatus optical communication system of claim 33, wherein the optical edge node corresponding to the protected end-system is operably coupled to automatically discover the at least one backup end-system using a predetermined auto-discovery mechanism.

35. (currently amended) The apparatus ~~optical communication system~~ of claim 33, wherein the optical edge node corresponding to the protected end-system is operably coupled to construct the failover tree to the backup end-system.

36. (currently amended) The apparatus ~~optical communication system~~ of claim 35, wherein the optical edge node corresponding to the protected end-system is operably coupled to determine a root node for the failover tree and construct the failover tree rooted at the root node.

37. (currently amended) The apparatus ~~optical communication system~~ of claim 36, wherein the optical edge node corresponding to the protected end-system is operably coupled to determine a root node for the failover tree by identifying a candidate node that is within a predetermined distance from the at least one backup end-system, constructing a shortest-path spanning tree from the candidate node to the at least one backup end-system, and selecting the candidate node as the root node if and only if the shortest-path spanning tree does not include any link from the protected end-system to the candidate node.

38. (currently amended) The apparatus ~~optical communication system~~ of claim 36, wherein the optical edge node corresponding to the protected end-system is operably coupled to send a setup request message specifying a failover tree structure to various nodes in the optical communication network.

39. (currently amended) The apparatus ~~optical communication system~~ of claim 38, wherein nodes associated with a primary lightpath to the primary end-system are operably coupled to reserve appropriate lightpath resources for the primary lightpath to the primary end-system.

40. (currently amended) The apparatus ~~optical communication system~~ of claim 38, wherein nodes associated with the failover tree are operably coupled to record the failover tree structure.

41. (cancelled)

42. (currently amended) The apparatus ~~optical communication system~~ of claim 32, wherein the optical edge node associated with the primary end-system is operably coupled to detect a degradation or failure affecting the primary end-system by at least one of:

monitoring a bearer channel between the primary end-system and a corresponding edge node in the optical communication network; and

querying the primary end-system by an optical service agent in said corresponding edge node.

43. (cancelled)

44. (currently amended) The apparatus ~~optical communication system~~ of claim 32, wherein a failover node of the failover tree is operably coupled to establish a backup lightpath from the failover node to a backup end-system and switch traffic to the backup lightpath by the failover node upon receiving the release message.

45. (currently amended) The apparatus ~~optical communication system~~ of claim 44, wherein the failover node is operably coupled to send a lightpath setup request message downstream toward the backup end-system in order to establish a backup lightpath.

46. (currently amended) The apparatus ~~optical communication system~~ of claim 45, wherein a number of nodes between the failover node and the backup end-system are operably coupled to reserve appropriate lightpath resources for the backup lightpath.

47. (currently amended) The apparatus ~~optical communication system~~ of claim 45, wherein the failover node is operably coupled to switch traffic to the backup lightpath upon receiving a connect message from the optical edge node associated -with the backup end-system.